



# VPC

## Vertical Turbine, Double-Case Pumps





*Experience In Motion*

## Unequaled hydraulic coverage and design flexibility

Flowserve VPC pumps are one of the world's most comprehensive lines of mixed-flow, diffuser-style, double-casing vertical turbine pumps. Available in single or multistage construction, as well as standard and ISO 13709/API 610-compliant designs, VPC pumps incorporate the proven hydraulics of the Flowserve VTP vertical turbine, wet-pit pump into a double-casing configuration. Multiple design configurations and broad hydraulic coverage ensure you get a cost-effective solution that precisely meets your application requirements.

- **Quick delivery and engineered flexibility** — VPC pumps come in a variety of standardized designs for quick turnarounds or they can be configured to order for custom specifications.
- **Unsurpassed hydraulic coverage** — Through design innovation and multiple legacy brands, the extensive hydraulic coverage meets nearly any duty condition requirement.
- **In-depth pump analysis** — A full array of structural (reed critical frequency, nozzle loads, seismic calculations), rotor dynamic (torsional, lateral) and thermal analyses are available to optimize pump performance and reliability.
- **Multiple design configurations** — VPC pumps are available in a variety of configurations to meet the requirements of a diverse range of applications and installation demands.
- **Wide range of material options** — Customers can select from numerous materials, including iron, bronze, stainless steel and super duplex, to maximize pump life in a range of applications.





## Application versatility

Flowserve VPC pumps are engineered to perform in a wide range of applications where a wet well is not available. They are designed for continuous duty and are particularly well suited for services with limited NPSH. VPC pumps meet the design requirements of international standards, including ANSI, AWWA, ASME and the Hydraulic Institute.

### Principal industries

- Power
- Oil and gas
- General industry
- Water resources
- Chemical

### Key applications


- Hydrocarbon booster
- Hydrocarbon transfer
- Pipeline booster
- Petrochemical transfer
- Condensate
- Water supply
- Water transfer
- Snowmaking
- Brine injection
- Heater drain

# Configurations and options

## Thrust bearing assembly

Axial thrust bearings withstand the total pump hydraulic thrust as well as the rotor weight. Self-lubricating, anti-friction bearings are utilized for standard applications.

- NEMA applications include a thrust bearing within the motor.
- IEC applications require the thrust bearing to be integral to the pump.




## Sealing configurations

Sealing configurations include packed box with flexible graphite packing and mechanical seals.

Mechanical seals provide increased reliability and functionality for VPC pumps:

- Pressures to 100 bar (1,450 psi)
- No leakage
- Easy access for maintenance and parts replacement
- Single and dual arrangements available
- Multiple seal piping plans available



## Multiple driver options

Flowserve VPC pumps are available with multiple driver options, including electric motors (solid or hollow shaft), diesel engines with right-angle gears and steam turbines.


## Suction configurations

VPC pumps are available with above- or belowground suction flanges to suit site conditions.


## Intake design

Flow-straightening vanes and vortex-suppression baskets can be installed within the barrel to optimize flow into the pump.

*Above-ground suction*



*Below-ground suction*



## ISO 13709/API 610 compliance


VPC pumps are available in a configuration that meets ISO 13709/API 610 standards. They are engineered for easy maintenance, high efficiency and long life in demanding applications found in the oil and gas and related industries. Key features include:

- Pressure ratings of at least 40 bar (600 psi) MAWP
- Weld neck flanges
- Precision, rigid adjustable flanged spacer coupling
- Studs and nuts
- One-piece pump shaft up to 6 m (20 ft)
- Dynamically balanced, keyed enclosed impellers
- Pinned wear rings
- API 610 forces and moments
- Elliptical bottom barrel

## Pipeline booster applications

VPC pumps are available in a configuration designed specifically for crude oil transportation. These robust pumps are engineered to provide high reliability and efficiency with little maintenance.

- Standardized design features to minimize manufacturing cycle time
- Suitable for variable-speed operation to optimize operating parameters
- High-efficiency design to reduce power consumption
- Strict quality assurance standards
- Expedited lead times through advanced procurement
- Customized engineering solutions
- Dedicated customer service teams
- API-grade materials with optional NACE compliance
- Option for two times ISO 13709/API 610 nozzle loads to withstand excessive forces and moments



ISO 13709/API 610-compliant configuration


# Performance capability

## Operating parameters

- Flows to 13,600 m<sup>3</sup>/h (60,000 gpm)
- Heads to 700 m (2,300 ft)
- Pressures to 100 bar (1,450 psi)
- Temperatures from -75°C to 230°C (-100°F to 450°F)



## Range chart



# Rebowl services

## Boost pump performance and reduce operating costs

Flowserve has developed an extensive rebowl services program that revitalizes the performance of vertical turbine pumps and reduces total pump operating costs. Whether restoring an aged pump or accommodating a change in operating conditions (capacity or head), customers are ensured high-quality upgrades that focus on prolonging equipment life and improving safety.

## Service for all makes and models

Flowserve rebowl services are available for any vertical turbine pump, regardless of model, age, service or manufacturer. Rebowl services include:

- Complete upfront inspection of all pump components
- Refurbishment of deteriorated components
- Upgraded replacement components
- Materials upgrades
- Warranty of both service and parts
- On-site installation service available

## Bottom-line benefits

- Improved pump performance
- Reduced power consumption
- Increased reliability
- Reduced maintenance costs
- Increased uptime

Refer to brochure PS-100-4 for more information about Flowserve's rebowl services.





Flowserve Corporation  
5215 North O'Connor Blvd.  
Suite 2300  
Irving, Texas 75039-5421 USA  
Telephone: +1 937 890 5839

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2020 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.

**PUBR000180 (EN/AQ)** May 2020